

# EJOT Self Drilling Screw JT2H-DP5 1/4-20x1-3/4



## Product Specifications

- > Threads Per Inch: 20
- > Head Style: Hex
- > Material: Alloy Steel ASTM A29 dual heat treated Grade 5
- > Drill Capacity: 0.125"-0.500" (Available in DP4)
- > Thread Major Dia: 0.246" (6.25 mm)
- > Thread Minor Dia: 0.186" (4.72 mm)
- > Corrosion protection: Salt spray 1000 hrs without red rust per ASTM B117

## Installation and Application

1. Do not use impact drivers.
2. The fasteners can be engaged in a steel substrate using a 3/8" hex socket bit and a clutch screw gun. The fastener should be installed with 0-1800 rpm max. Be cautious as not to over drive the fastener and make sure that the thread is engaged with the base material.
3. To have enough penetration, ensure that first three full threads behind the drill point protrude through the base material.

## Storage

Fasteners should be stored in the original packaging.

## Precautions

Always use eye protection to reduce safety risks.

## Product Properties

Steel gauge	Ultimate Pull Out Strength (lbf)	Steel gauge	Ultimate Pullover Strength (lbf)	Ultimate Tensile Test Strength (lbf)
12ga	1182	12ga	4090	4491
3/16"	2666	3/16"	4333	Ultimate Shear Strength (lbf)
3/8"	4344	3/8"	4390	2694

# EJOT Self Drilling Screw JT2H-DP5 1/4-20x1-3/4


## Product Properties

Steel gauge	Lap shear (lbf)
24G/12G	821
18G/12G	2060
16G/14G	1993
14G/16G	2020
12G/24G	419
12G/22G	745
12G/20G	1062
12G/18G	1662
11G/26G	361
11G/18G	1329
11G/12G	2489

## Product Available Lengths and SKU #s

Order Description	Length (L) Inch	Thread Length (L1) inch	Part No.
JT2H-DP5 1/4-20 x 1-3/4	1-3/4	Fully Threaded	3555558596

## Product Drawing



The data sheet highlights EJOT products and specifications. The mentioned values are subject to change without notice and are based on tested samples that may vary within applicable tolerances. EJOT takes responsibility for ensuring that the quality materials meets published EJOT product specifications. EJOT does not accept any liability for structural failure or resultant damages. A structural engineer should be consulted with before installation to ensure structural soundness or structural ability. No EJOT representative is authorized to vary this disclaimer.

# Self drilling screw JT2H

## Applications and Properties

- > JT2 is designed to drill quickly, easily, and consistently into 0.036" to 0.187"
- > Available in lengths from 3/4" to 1-1/2" and is available with DB/s extra thick 5 micron electro zinc plating or in DB's Mag Life Coating
- > Available with or without our EPDM Sealing Washer bonded to Galvanized Steel back to help prevent leaks.



Article number	Size	Head Diameter (inch)	Drill Point	Head Size	Head Style	Drilling Capacity (inch)
3555558352	10-16 X 3/4	0.400	3	5/16	Hex	0.036-0.175
3555558355	10-16 X 1-1/2	0.400	3	5/16	Hex	0.036-0.175
3555558356	10-16 X 2	0.400	3	5/16	Hex	0.036-0.175
3555558357	10-16 X 2-1/2	0.400	3	5/16	Hex	0.036-0.175
3555559352	10-16 X 3/4	0.370	3	2	PPH	0.036-0.175
3555559362	10-16 X 3/4	0.470	3	2	PWH	0.036-0.175
3555559364	10-16 X 1-1/4	0.470	3	2	PWH	0.036-0.175
3555558372	12-14 X 7/8	0.420	3	5/16	Hex	0.036-0.175
3555558373	12-14 X 1	0.420	3	5/16	Hex	0.036-0.175
3555558374	12-14 X 1-1/4	0.420	3	5/16	Hex	0.036-0.175
3555558375	12-14 X 1-1/2	0.420	3	5/16	Hex	0.036-0.175
3555558376	12-14 X 2	0.420	3	5/16	Hex	0.036-0.175
3555558377	12-14 X 2-1/2	0.420	3	5/16	Hex	0.036-0.175
3555558378	12-14 X 3	0.420	3	5/16	Hex	0.036-0.175
3555558272	12-14 X 7/8	0.420	2	5/16	Hex	0.030-0.110

# Self drilling screw JT2H

Article number	Size	Head Diameter (inch)	Drill Point	Head Size	Head Style	Drilling Capacity (inch)
3555558273	12-14 X 1	0.420	2	5/16	Hex	0.030-0.110
3555558274	12-14 X 1-1/4	0.420	2	5/16	Hex	0.030-0.110
3555558275	12-14 X 1-1/2	0.420	2	5/16	Hex	0.030-0.110
3555558276	12-14 X 2	0.420	2	5/16	Hex	0.030-0.110
3555559373	12-14 X 1	0.400	3	3	PUFH	0.036-0.175
3555559374	12-14 X 1-1/4	0.400	3	3	PUFH	0.036-0.175
3555559375	12-14 X 1-1/2	0.400	3	3	PUFH	0.036-0.175
3555558576	12-24 X 1-3/4	0.420	5	5/16	Hex	0.125-0.500
3555558393	1/4-14 X 1	0.500	3	3/8	Hex	0.036-0.175
3555558395	1/4-14 X 1-1/2	0.500	3	3/8	Hex	0.036-0.175
3555558396	1/4-14 X 2	0.500	3	3/8	Hex	0.036-0.175
3555558494	1/4-20 X 1-1/8	0.500	4	3/8	Hex	0.125-0.250
3555558495	1/4-20 X 1-1/2	0.500	4	3/8	Hex	0.125-0.250
3555558496	1/4-20 X 2	0.500	4	3/8	Hex	0.125-0.250
3555558497	1/4-20 X 2-1/2	0.500	4	3/8	Hex	0.125-0.250
3555558498	1/4-20 X 3-3/8	0.500	4	3/8	Hex	0.125-0.250
3555558499	1/4-20 X 4	0.500	4	3/8	Hex	0.125-0.250
3555558596	1/4-20 X 1-3/4	0.500	5	3/8	Hex	0.125-0.500
3555559498	1/4-20 X 3	0.460	4	3	PUFH	0.125-0.250
3555559499	1/4-20 X 4	0.460	4	3	PUFH	0.125-0.250
3555558405	5/16-24 X 1-1/2	0.520	4	3/8	Hex	0.125-0.250
3555558406	5/16-24 X 2	0.520	4	3/8	Hex	0.125-0.250
3555558409	5/16-24 X 3-1/4	0.520	4	3/8	Hex	0.125-0.250

# Self drilling screw JT2H

The data sheet highlights EJOT products and specifications. The mentioned values are subject to change without notice and are based on tested samples that may vary within applicable tolerances. EJOT takes responsibility for ensuring that the quality materials meets published EJOT product specifications. EJOT does not accept any liability for structural failure or resultant damages. A structural engineer should be consulted with before installation to ensure structural soundness or structural ability. No EJOT representative is authorized to vary this disclaimer.